

3000 R / 3150 RJ

Specifications



Type	3000 RB	3150 RJ - flyjib	3000 RBD
Max. working height	29.7 m	31.1 m	29.7 m
Max. outreach	12.6 m		12.6 m
Basket size	1.25x0.8x1.1 m		1.25x0.8x1.1 m
Travelling length	8.10/7.28 m	8.40/7.65 m	8.10/7.25 m
Travelling height	1.99 m		1.99 m
Travelling width	1.10 m		1.10 m
Operational width	4.60 / 3.75 m		4.60 / 3.75 m
Crawler track length	1.74 m		1.74 m
Battery	24 V 400 Ah/5h		24 V 200 Ah/5h
Charger	24 V 30 A		24 V 30 A
Transformer	24 V 50 A		O
Generator			24 V 22 A
Turntable basket ±	41°		41°
Rotation ±	355°		355°
Gradeability across slope up to	25 % 14.0 °		25 % 14.0 °
Gradeability up and down slope up to	35 % 19.3 °		35 % 19.3 °
Deployment ability procent	40 % 21.8 °		40 % 21.8 °
Number of supporting rollers	4		4
Max. basket load	200 kg		200 kg
Total weight approx	3900 kg	4000 kg	3900 kg
Diesel motor			14 kW 18.8 hp

Adjustable tracks	O
Automatic stabilizer levelling system up and down	O
Flash lights - crawler	O
Jib-movable	O
Non-marking tracks	O
Special color crawler	O
Spotlight in basket O16	O
Two-charger system with boost effect	O
Wireless remote control (drive only)	O

O Option